



Wind Speed

ADJUSTABLE MAGNETIC BASE DRILLING MACHINE WS-6000PM

- The drilling position can be adjusted vertically by 10 mm after attaching to the iron plate.
- After attaching to the iron plate, the drilling machine can be rotated left and right by amazing 18 degrees each.



MACHINE SPECIFICATIONS

Model	WS-6000PM	
Voltage (Single Phase)	100 ~ 120V AC	220 ~ 240V AC
	50 / 60 HZ	50 / 60 HZ
Ampacity	20A	10A
Power Consumption	2050W	
No-Load Speed	High Speed 750rpm	Low Speed 450rpm
Adjustable in Height for Max. Stroke	150mm	
Machine Dimensions	340 x 280 x 550 mm (Lowest)	
Magnet Specifications	22540N (2300kgf)	210 x 100 x 64 mm
Weight	26kg	

CUTTER SPECIFICATIONS FOR DRILLING MACHINE

Annular Cutter	Outer Diameter : 18-60 mm
	Plate Thickness : 6-75 mm
Twist Drill	Max Diameter : 16 mm

STANDARD ACCESSORIES

OPTIONAL ACCESSORIES

1. Pilot Pin 8 x 91 mm / 8 x 112 mm : 1pc
2. Double Open End Wrench : 1pc
3. 2.5 / 6.0 mm Hex. Key Wrench : 1pc
4. Operating Handle : 3pcs
5. Lifting Handle : 1pc
6. Carbon Brush : 1pc
7. Fixed screw : 1pc
8. Operation Manual : 1set

1. Drill Chuck and Adaptor Arbour
2. Annular Cutter 18-60 mm
3. Twist Drill (1-16 mm)
4. Twist Drill Adaptor
5. Safety Chain
6. Miyanach X-1 Cutting Oil 2L / per can

MIYANACH IND. CO., LTD.

No.16, Lane 247 Sec.3, Changnan Rd., Fenyuan T., Changhua Co. 502, Taiwan

<http://www.miyanach.com> Tel:886-49-2526448 Fax:+886-49-2528092



ISO9001